

### Termokurczliwe kaptury uszczelniające typu ECE



Symbol katalogowy	H x B [mm]		d [mm]		Zastosowanie do rur preizolowanych		
	max	min	max	min	typ rury	h x b [mm]	s [mm]
<b>ECE 25</b>	155 x 112	109 x 78	38	27	2 x DN 25	144 x 99	20
<b>ECE 32</b>	195 x 144	136 x 98	48	34	2 x DN 32	184 x 131	20
<b>ECE 40</b>	195 x 144	136 x 98	54	42	2 x DN 40	184 x 131	20
<b>ECE 50</b>	225 x 149	157 x 106	70	48	2 x DN 50	211 x 136	25
<b>ECE 65</b>	275 x 190	192 x 133	82	60	2 x DN 65	261 x 176	25
<b>ECE 80</b>	305 x 210	214 x 147	95	76	2 x DN 80	292 x 196	30
<b>ECE 100</b>	385 x 253	269 x 177	120	98	2 x DN 100	367 x 238	30
<b>ECE 125</b>	435 x 284	305 x 198	145	125	2 x DN 125	418 x 267	35
<b>ECE 150</b>	490 x 315	343 x 221	172	148	2 x DN 150	475 x 298	45

kaptur termokurczliwy

rura preizolowana

